

Institutional wheels



Series 68 /1/P

Series 67 /1/P

								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
67/050/18/1/P	50	18	69	60 x 60	48 x 48/38 x 38	6	23	40
67/075/25/1/P	75	25	100	60 x 60	48 x 48/38 x 38	6	30	60
67/100/32/1/P	100	32	135	95 x 70	76 x 52/72 x 45	9	43	90
67/125/32/1/P	125	32	160	95 x 70	76 x 52/72 x 45	9	41	110
67/150/32/1/P	150	32	185	95 x 70	76 x 52/72 x 45	9	36	110
67/050/18/5/P FAD	50	18	69	60 x 60	46 x 46/40 x 40	6	25	40
67/075/25/5/P FAD	75	25	100	60 x 60	48 x 48/38 x 38	6	30	60
67/100/32/5/P FAD	100	32	135	95 x 70	76 x 52/72 x 45	9	43	90
67/125/32/5/P FAD	125	32	160	95 x 70	76 x 52/72 x 45	9	41	110
67/150/32/5/P FAD	150	32	185	95 x 70	76 x 52/72 x 45	9	36	110

Institutional swivel castors with thermoplastic rubber wheels

Wheels series 85 with plain bearing (/1) or ball bearings with thread guards (/5/P FAD), see page 130.

								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
68/050/18/1/P	50	18	69	60 x 60	48 x 48/38 x 38	6		40
68/075/25/1/P	75	25	100	60 x 60	48 x 48/38 x 38	6		60
68/100/32/1/P	100	32	135	95 x 77	76 x 52/72 x 45	9		90
68/125/32/1/P	125	32	160	95 x 77	76 x 52/72 x 45	9		110
68/150/32/1/P	150	32	185	95 x 77	76 x 52/72 x 45	9		110
68/050/18/5/P FAD	50	18	70	60 x 60	48 x 48/38 x 38	6		40
68/075/25/5/P FAD	75	25	100	60 x 60	48 x 48/38 x 38	6		60
68/100/32/5/P FAD	100	32	135	95 x 77	76 x 52/72 x 45	9		90
68/125/32/5/P FAD	125	32	160	95 x 77	76 x 52/72 x 45	9		110
68/150/32/5/P FAD	150	32	185	95 x 77	76 x 52/72 x 45	9		110

Institutional fixed castors



Institutional swivel castor brackets with a load capacity of up to 110 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearing and riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device
Code: 67 F/...P

