

Institutional wheels



Series 68 PU

Series 67 PU/R

Series 67 PU

									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
67 PU/050/18/1/P	50	18	69	60 x 60	48 x 48/38 x 38	6	–	21	40
67 PU/075/24/1/P	75	24	100	60 x 60	48 x 48/38 x 38	6	–	30	60
67 PU/100/30/1/P	100	30	135	95 x 70	76 x 52/72 x 45	9	–	41	100
67 PU/125/30/1/P	125	30	160	95 x 70	76 x 52/72 x 45	9	–	39	125
67 PU/075/24/5/P	75	24	100	60 x 60	48 x 48/38 x 38	6	–	30	60
67 PU/100/30/5/P	100	30	135	95 x 70	76 x 52/72 x 45	9	–	41	100
67 PU/125/30/5/P	125	30	160	95 x 70	76 x 52/72 x 45	9	–	39	125
67 PU/050/18/1/R	50	18	69	–	–	–	10	21	40
67 PU/075/24/1/R	75	24	98	–	–	–	10	30	60
67 PU/100/30/1/R	100	30	132	–	–	–	12	41	100
67 PU/125/30/1/R	125	30	160	–	–	–	12	39	125
67 PU/075/24/5/R	75	24	98	–	–	–	10	30	60
67 PU/100/30/5/R	100	30	132	–	–	–	12	41	100
67 PU/125/30/5/R	125	30	160	–	–	–	12	39	125

Institutional swivel castors with PEVOTHAN® wheels

Wheels series 85 PU with plain bearing (/1) or ball bearings (/5), see page 130.

							
Article code	mm	mm	mm	mm	mm	mm	kg
68 PU/050/18/1/P	50	18	69	60 x 60	48 x 48/38 x 38	6	40
68 PU/075/24/1/P	75	24	100	67 x 60	48 x 48/38 x 38	6	60
68 PU/100/30/1/P	100	30	135	95 x 70	76 x 52/72 x 45	9	100
68 PU/125/30/1/P	125	30	160	95 x 70	76 x 52/72 x 45	9	125
68 PU/075/24/5/P	75	24	100	67 x 60	48 x 48/38 x 38	6	60
68 PU/100/30/5/P	100	30	135	95 x 70	76 x 52/72 x 45	9	100
68 PU/125/30/5/P	125	30	160	95 x 70	76 x 52/72 x 45	9	125

Institutional fixed castors

Matching the swivel castors with top plate (/P).



Institutional swivel castor brackets with a load capacity of up to 125 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings and riveted kingpin. With either plate or bolt hole fitting. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device
Code: 67 F PU/...P

single bolt hole/total lock
Code: 67 F PU/...R

