

# PE·VO·LON® industrial castors



Series PB/1

Series PL/1

Article code	mm	mm	mm	mm	mm	mm	mm	kg
PL 050/25/1	50	25	72	80 x 60	60 x 40	7	21	75
PL 070/30/1 L	70	30	103	105 x 85	80 x 60	9	38	120
PL 080/30/1 L	80	30	108	105 x 85	80 x 60	9	38	120
PL 100/34/1 L	100	34	128	105 x 85	80 x 60	9	38	125
PL 100/40/1	100	40	126	135 x 110	105 x 80	11	40	300
PL 125/40/1 L	125	40	155	105 x 85	80 x 60	9	45	180
PL 125/40/1	125	40	164	135 x 110	105 x 80	11	55	300
PL 150/42/1	150	42	194	135 x 110	105 x 80	11	55	300
PL 175/50/1	175	50	217	135 x 110	105 x 80	11	55	350
PL 200/50/1	200	50	239	135 x 110	105 x 80	11	55	400
PL 250/50/1	250	50	290	135 x 110	105 x 80	11	55	400


## Industrial swivel castors with PEVOLON® wheels

Wheels series A/B with plain bearing (/1), see page 36/39.

Article code	mm	mm	mm	mm	mm	mm	kg
PB 050/25/1	50	25	72	93 x 50	71 x 24	6	75
PB 070/30/1 L	70	30	103	105 x 85	80 x 60	9	120
PB 080/30/1 L	80	30	108	105 x 85	80 x 60	9	120
PB 100/34/1 L	100	34	128	105 x 85	80 x 60	9	125
PB 100/40/1	100	40	126	135 x 110	105 x 80	11	300
PB 125/40/1	125	40	164	135 x 110	105 x 80	11	300
PB 125/40/1 L	125	40	155	105 x 85	80 x 60	9	180
PB 150/42/1	150	42	194	135 x 110	105 x 80	11	300
PB 175/50/1	175	50	217	135 x 110	105 x 80	11	350
PB 200/50/1	200	50	239	135 x 110	105 x 80	11	400
PB 250/50/1	250	50	290	135 x 110	105 x 80	11	400

1-way directional lock only available for plate 135 x 110 mm.  
ALLSTOP total locking device not available for wheel diameter 50 mm and 70 mm.

## Industrial fixed castors



## Industrial swivel castor brackets with a load capacity of up to 400 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

\* with locking device code: PLFZ...

**ALLSTOP total locking device**  
Code: PLF...

**directional lock**  
Code: PL.../...TRIF

**single bolt hole**  
Code: PL...R

**foot protection**  
Code: ...PRO

**single bolt hole/total lock**  
Code: PLFZ...R

**stem fitting**  
Code: PLZ...\*

PEVOLON® - PEVOLASTIC®  
PEVOTHA®  
Solid rubber wheels and castors  
Electrically conductive wheels and castors  
VULKOLAN® - PEVOPIUR® - PEVODYN® - Soft  
Stainless steel castors  
Institutional wheels and castors  
Conveyor/guiding rollers and ball units  
Profile rollers  
Pallet rollers  
Press-on tyres