

Solid rubber heavy-duty drive wheels

Series 70/A



						
Article code	mm	mm	mm	mm	mm	kg
70 A/300/075/240/2/50 H7	300	75	65	78	50	700
70 A/360/060/270/2/40 H7	360	60	70	66	40	750
70 A/360/075/270/2/45 H7	360	75	100	66	45	950
70 A/360/085/270/2/50 H7	360	85	95	78	50	1.050
70 A/360/150/270/2/50 H7	360	150	160	78	50	1.900
70 A/405/065/305/2/50 H7	405	65	80	78	50	900
70 A/405/130/305/2/50 H7	405	130	130	78	50	1.500
70 A/415/075/305/2/50 H7	415	75	90	78	50	1.000
70 A/415/090/305/2/60 H7	415	90	100	91	60	1.150
70 A/415/100/305/2/55 H7	415	100	120	97	55	1.250
70 A/425/150/305/2/70 H7	425	150	160	102	70	1.800
70 A/500/085/370/2/60 H7	500	85	95	91	60	1.300
70 A/520/100/370/2/60 H7	520	100	95	91	60	1.525
70 A/540/200/410/2/60 H7	540	200	210	91	60	3.270
70 A/550/160/410/2/50 J7	550	160	160	78	50	2.250
70 A/560/100/410/2/60 H7	560	100	95	91	60	1.600
70 A/590/120/410/2/70 H7	590	120	95	104	70	1.900
70 A/610/150/410/2/60 H7	610	150	120	91	60	2.250
70 A/620/200/410/2/70 H7	620	200	180	104	70	3.000
70 A/645/300/410/2/75 J7	645	300	300	110	75	6.000

Heavy-duty solid rubber drive wheels

Rim, designed as a stable welded steel construction with bore and keyway according to DIN 6885 press-on and replaceable steel band solid rubber tyre.

Heavy-duty solid rubber wheels with bolt hole fitting or for the reception of clamping sets available on request.