

Pneumatic tyred wheels

Series 91



						
Article code	mm	mm	Tyre	mm	mm	kg
91/180/045/3/20/60 R	180	45	7 x 1 3/4 2PR rib	60	20	75
91/200/050/3/20/50 R	200	50	200 x 50 2PR rib	50	20	75
91/200/050/1/20/58 KR	200	50	200 x 50 2PR rib	58	20	75
91/200/050/3/20/60 R	200	50	200 x 50 2PR rib	60	20	75
91/210/065/3/20/50 R	210	65	2.50 - 3 2PR rib	50	20	100
91/210/065/3/20/75 R	210	65	2.50 - 3 2PR rib	75	20	100
91/220/070/3/20/75 S	220	70	2.50 - 4 2PR block	75	20	130
91/260/085/3/20/75 KS*	260	85	3.00 - 4 2PR block	75	20	125
91/260/085/3/25/75 S	260	85	3.00 - 4 2PR block	75	25	200
91/260/085/3/25/75 KS	260	85	3.00 - 4 2PR block	75	25	200
91/260/085/5/20/75 R	260	85	3.00 - 4 2PR rib	75	20	200
91/260/085/3/20/50 R	260	85	3.00 - 4 2PR rib	50	20	200
91/260/085/1/20/50 KS	260	85	3.00 - 4 2PR block	50	20	200
91/260/085/5/25/50 S	260	85	3.00 - 4 2PR block	50	25	200
91/260/085/1/20/75 KS*	260	85	3.00 - 4 2PR block	75	20	200
91/260/085/1/25/75 KS	260	85	3.00 - 4 2PR block	75	25	180
91/260/085/3/20/50 S	260	85	3.00 - 4 2PR block	50	20	200
91/260/085/3/20/75 S	260	85	3.00 - 4 2PR block	75	20	200
91/260/085/3/20/60 S**	260	85	3.00 - 4 2PR block	60	20	200
91/260/085/3/20/88 S	260	85	3.00 - 4 4PR block	88	20	200
91/260/085/3/25/88 S	260	85	3.00 - 4 2PR block	88	25	200
91/400/100/3/25/75 R	400	100	4.00 - 8 2PR rib	75	25	200
91/400/100/3/25/88 R	400	100	4.00 - 8 2PR rib	88	25	250
91/400/100/1/20/75 KS	400	100	4.00 - 8 2PR block	75	20	250
91/400/100/1/20/88 KS	400	100	4.00 - 8 4PR block	88	20	250
91/400/100/3/20/88 KR*	400	100	4.00 - 8 4PR rib	88	20	250
91/400/100/5/20/88 R	400	100	4.00 - 8 2PR rib	88	20	250
91/400/100/5/25/88 R	400	100	4.00 - 8 4PR rib	88	25	250

Pneumatic tyred transport wheels

Plastic (K) or pressed steel rim, with plain bearing (/1), roller bearing (/3) or ball bearings (/5).