

Solid rubber industrial castors



Series 32/3

Series 31/3

								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
31/080/25/3 L	80	25	108	105 x 85	80 x 60	9	38	50
31/100/30/3 L	100	30	128	105 x 85	80 x 60	9	38	70
31/125/37/3 L	125	37	155	105 x 85	80 x 60	9	45	100
31/125/37/3	125	38	164	135 x 110	105 x 80	11	55	100
31/160/40/3	160	40	199	135 x 110	105 x 80	11	55	135
31/180/45/3	180	45	219	135 x 110	105 x 80	11	55	170
31/200/50/3	200	50	239	135 x 110	105 x 80	11	55	205
31/250/60/3	250	58	290	135 x 110	105 x 80	11	55	295


Industrial swivel castors with solid rubber wheels in standard quality

Wheels series 80 with roller bearing (/3), see page 60.

							
Article code	mm	mm	mm	mm	mm	mm	kg
32/080/25/3 L	80	25	108	105 x 85	80 x 60	9	50
32/100/30/3 L	100	30	128	105 x 85	80 x 60	9	70
32/125/37/3 L	125	37	155	105 x 85	80 x 60	9	100
32/125/37/3	125	38	164	135 x 110	105 x 80	11	100
32/160/40/3	160	40	199	135 x 110	105 x 80	11	135
32/180/45/3	180	45	219	135 x 110	105 x 80	11	170
32/200/50/3	200	50	239	135 x 110	105 x 80	11	205
32/250/60/3	250	58	290	135 x 110	105 x 80	11	295

1-way directional lock only available for plate 135 x 110 mm.

Industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 295 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

* with ALLSTOP total locking device code: 31 FZ/..

ALLSTOP total locking device
Code: 31 F/...



single bolt hole
Code: 31/...R



single bolt hole/total lock
Code: 31 F/...R



directional lock
Code: 31/...1RIF



foot protection
Code: ...PRO



stem fitting
Code: 31 Z/...*

