










Solid rubber **industrial castors**











Series 28 Stage

Series 27 Stage


								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
27 STAGE/080/34/3 L	80	34	101	105 x 80	80 x 60	9	36	150
27 STAGE/100/36/3 L	100	36	125	105 x 80	80 x 60	9	36	200
27 STAGE/125/36/3 L	125	36	155	105 x 80	80 x 60	9	36	250
27 STAGE/160/50/3	160	50	199	135 x 110	105 x 80	11	55	300

Industrial swivel castors with ELASTIC solid rubber wheels (Blue Wheel)

Wheels series 74 with roller bearing (1/3), see page 62.

							
Article code	mm	mm	mm	mm	mm	mm	kg
28 STAGE/080/34/3 L	80	34	101	102 x 87	80 x 60	9	150
28 STAGE/100/36/3 L	100	36	125	102 x 87	80 x 60	9	200
28 STAGE/125/36/3 L	125	36	155	102 x 87	80 x 60	9	250
28 STAGE/160/50/3	160	50	199	135 x 110	105 x 80	11	300

Industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 300 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device
Code: 27 F STAGE/...



single bolt hole
Code: 27 STAGE/...R



single bolt hole/total lock
Code: 27 F STAGE/...R

