

PE·VO·THAN® electrically conductive institutional castors

Series 68 XPU

Series 67 XPU/R

Series 67 XPU/P



Institutional swivel castors with electrically conductive PEVOTHAN® wheels

Wheels series 85 XPU
(80° Shore A) with plain
bearing (/1), see page 80.


Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
67 XPU/075/24/1/P	75	24	100	60 x 60	48 x 48/38 x 38	6	–	30	60
67 XPU/100/30/1/P	100	30	135	95 x 70	76 x 52/72 x 45	9	–	41	100
67 XPU/125/30/1/P	125	30	160	95 x 70	76 x 52/72 x 45	9	–	39	125
67 XPU/075/24/1/R	75	24	98	–	–	–	10	30	60
67 XPU/100/30/1/R	100	30	132	–	–	–	12	41	100
67 XPU/125/30/1/R	125	30	160	–	–	–	12	39	125

Fixing devices for institutional swivel castors with bolt hole fitting, see page 133.

Article code	mm	mm	mm	mm	mm	mm	kg
68 XPU/075/24/1/P	75	24	100	67 x 60	48 x 48/38 x 38	6	60
68 XPU/100/30/1/P	100	30	135	95 x 70	76 x 52/72 x 45	9	100
68 XPU/125/30/1/P	125	30	160	95 x 70	76 x 52/72 x 45	9	125

Institutional fixed castors

Matching the swivel castors with
top plate (/P).



Institutional swivel castor brackets with a load capacity of up to 125 kg

Housings made of pressed steel,
zinc and chromated. Swivel
head with double ball bearings
and riveted kingpin. ALLSTOP total
locking device on the trailing side
of the housing, blocks rolling and
swivel motion simultaneously.

ALLSTOP total locking device
Code: 67 F XPU/.../P



single bolt hole/total lock
Code: 67 F XPU/...R



PEVOTHAN®
PEVOTHAN®

Solid rubber
wheels and castors

Electrically conductive
wheels and castors

VULVOLAN® • PEVOPUR®
PEVODYN® - Soft

Stainless steel castors

Institutional
wheels and castors

Conveyor/guiding
rollers and ball units

Profile rollers

Pallet rollers

Press-on tyres