

PE·VO·THAN® electrically conductive industrial castors

Series 68 XPU NI

Series 67 XPU NI/R

Series 67 XPU NI/P



Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
67 XPU NI/075/24/1/P	75	24	107	95 x 70	75 x 45/72 x 52	8	–	33	60
67 XPU NI/100/30/1/P	100	30	135	95 x 70	75 x 45/72 x 52	8	–	41	100
67 XPU NI/125/30/1/P	125	30	161	95 x 70	75 x 45/72 x 52	8	–	39	125

67 XPU NI/075/24/1/R	75	24	98	–	–	–	10	30	60
67 XPU NI/100/30/1/R	100	30	132	–	–	–	12	41	100
67 XPU NI/125/30/1/R	125	30	160	–	–	–	12	39	125

Fixing devices for institutional swivel castors with bolt hole fitting, see page 127.

Article code	mm	mm	mm	mm	mm	mm	kg
68 XPU NI/075/24/1/P	75	24	107	95 x 77	75 x 45/72 x 52	8	60
68 XPU NI/100/30/1/P	100	30	135	95 x 77	75 x 45/72 x 52	8	100
68 XPU NI/125/30/1/P	125	30	161	95 x 77	75 x 45/72 x 52	8	125

ALLSTOP total locking device
Code: 67 F XPU NI/.../P



single bolt hole/total lock
Code: 67 F XPU NI/.../R




Stainless steel institutional swivel castors with electrically conductive PEVO·THAN® wheels

Wheels series 85 XPU (80° Shore A) with plain bearing (/1), see page 80.

Stainless steel institutional fixed castors

Matching the swivel castors with top plate (/P).



Institutional swivel castor brackets with a load capacity of up to 125 kg

Housings made of stainless pressed steel. Swivel head with double ball bearing and riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

PEVO·THAN®
PEVO·THAN®

Solid rubber
wheels and castors

Electrically conductive
wheels and castors

VULKOLAN® • PEVO·THAN®
PEVO·THAN® / Soft

Stainless steel castors

Institutional
wheels and castors

Conveyor/guiding
rollers and ball units

Profile rollers

Pallet rollers

Press-on tyres