










# PE·VO·THAN® electrically conductive stainless steel industrial castors











Series 32 XPU NI/3R

Series 31 XPU NI/3R


								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
31 XPU NI/080/35/3R L	80	35	108	105 x 85	80 x 60	9	38	100
31 XPU NI/100/34/3R L	100	34	128	105 x 85	80 x 60	9	38	140
31 XPU NI/125/37/3R L	125	37	155	105 x 85	80 x 60	9	45	180
31 XPU NI/150/45/3R	150	45	192	135 x 110	105 x 80	11	55	225

## Stainless steel industrial swivel castors with electrically conductive PEVOTHAN® wheels

Wheels series 89 XPU (80° Shore A) with stainless roller bearing (/3R), see page 80.

							
Article code	mm	mm	mm	mm	mm	mm	kg
32 XPU NI/080/35/3R L	80	35	108	105 x 85	80 x 60	9	100
32 XPU NI/100/34/3R L	100	34	128	105 x 85	80 x 60	9	140
32 XPU NI/125/37/3R L	125	37	155	105 x 85	80 x 60	9	180
32 XPU NI/150/45/3R	150	45	192	135 x 110	105 x 80	11	225

## Stainless steel industrial fixed castors



## Industrial swivel castor brackets with a load capacity of up to 225 kg

Housings made of stainless pressed steel. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device  
Code: 31 F XPU NI/...

single bolt hole  
Code: 31 XPU NI/...R

single bolt hole/total lock  
Code: 31 F XPU NI/...R



stem fitting  
Code: 31 Z XPU NI/...

stem fitting/total locking device  
Code: 31 FZ XPU NI/...

